

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/SE05/000018

International filing date: 11 January 2005 (11.01.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB
Number: 0405421.9
Filing date: 10 March 2004 (10.03.2004)

Date of receipt at the International Bureau: 14 February 2005 (14.02.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



PCT / SE 2005 / 0 0 0 0 1 8

1 0 -02- 2005



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ


I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

I also certify that the attached copy of the request for grant of a Patent (Form 1/77) bears an amendment, effected by this office, following a request by the applicant and agreed to by the Comptroller-General.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.




Signed

AmBrewster

Dated 10 January 2005





1/77

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

P18375GB - NHF/hs

2. Patent application number

(The Patent Office will fill this part in)

0405421.9

10 MAR 2004

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Autoliv Development AB - note minute 30-7-04.
S-447 83 VARGARDA
Sweden

Patents ADP number (if you know it)

321018012

If the applicant is a corporate body, give the country/state of its incorporation

Sweden

4. Title of the invention

"IMPROVEMENTS IN OR RELATING TO A STEERING WHEEL ARRANGEMENT"

5. Name of your agent (if you have one)

Forrester Ketley & Co.

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Forrester House
52 Bounds Green Road
London
N11 2EY

Patents ADP number (if you know it)

133001 ✓

6. Priority: Complete this section if you are declaring priority from one or more earlier patent applications, filed in the last 12 months.

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. Divisionals, etc: Complete this section only if this application is a divisional application or resulted from an entitlement dispute (see note f).

Number of earlier UK application

Date of filing
(day / month / year)

8. Is a Patents Form 7/77 (Statement of inventorship and of right to grant of a patent) required in support of this request?

Answer YES if:

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

Otherwise answer NO (See note d)

Patents Form 1/77

9. ☐ accompanying documents: A patent application must include a description of the invention. Not counting duplicates, please enter the number of pages of each item accompanying this form:

Continuation sheets of this form

Description 9

Claim(s) 2

Abstract 1

Drawing(s) 7 + 7 *ll*

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for a preliminary examination and search (Patents Form 9/77) X

Request for a substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature(s) Forrester Ketley & Co.

Forrester Ketley & Co.

Date 9 March 2004

12. Name, daytime telephone number and e-mail address, if any, of person to contact in the United Kingdom

FRANKLAND, Nigel H.
(020) 8889 6622

fk london@forresters.co.uk

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered YES in part 8, a Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) Part 7 should only be completed when a divisional application is being made under section 15(4), or when an application is being made under section 8(3), 12(6) or 37(4) following an entitlement dispute. By completing part 7 you are requesting that this application takes the same filing date as an earlier UK application. If you want the new application to have the same priority date(s) as the earlier UK application, you should also complete part 6 with the priority details.

Patents Form 1/77

PATENTS ACT 1977

P18375GB - NHF/SJP/jw

5 DESCRIPTION OF INVENTION

**"IMPROVEMENTS IN OR RELATING TO A STEERING WHEEL
ARRANGEMENT"**

10

THE PRESENT INVENTION relates to a steering wheel arrangement.

15 It has been proposed previously to provide a steering wheel unit for use in a motor vehicle. The steering wheel is mounted to rotate relative to a fixed housing, the axis upon which the steering wheel rotates is offset from the axis of the steering column. The steering column carries a pinion gear. The steering wheel carries a ring gear which meshes with part of the pinion gear. As the steering wheel rotates, so the steering column is rotated.

20

In one embodiment of a steering wheel of this type, it is possible to mount a central air-bag unit, with the air-bag unit remaining stationary while the steering wheel rotates. This sort of arrangement enables the specially-shaped air-bag to be utilised and also facilitates the mounting of control buttons
25 or the like on the upper surface of the air-bag unit.

A typical steering wheel arrangement incorporates a large number of parts, and there may be some cumulative tolerances when many parts are put together. This can be particularly bad in the above-mentioned type of steering

wheel arrangement because there may be some "play" between the pinion on the steering column and the ring gear provided on the steering wheel. This gives the steering wheel an undesirable "feel" when the motor vehicle is being driven.

5

The present invention seeks to provide an improved steering wheel arrangement.

According to the present invention, there is provided a steering wheel arrangement, the steering wheel arrangement incorporating a fixed element, the fixed element carrying a first annular bearing, the annular bearing supporting a steering wheel for rotation relative to the fixed element, the fixed element also carrying a second bearing, the second bearing rotatably supporting a component to be connected to part of the steering column of a vehicle, the bearings each being retained, to the fixed element, by means of a first resilient retaining element, and the first bearing being retained to the steering wheel by a second resilient retaining element.

Preferably, the fixed element has a housing part with an upper surface, the upper surface having at least two levels, the outer periphery of the upper surface defining a wall, the first bearing being mounted to that wall, the upper surface defining an opening having a side wall, the second bearing being mounted to that side wall; wherein the first retaining element comprises a plate which lies over the upper surface, the plate having a part which is resiliently biased into contact with part of the first bearing and with part of the second bearing.

Advantageously, the plate has two arcuate sections located to either side of an aperture, one arcuate section being provided with retaining studs to secure

the plate to the fixed element, the other arcuate section being resiliently connected to the first arcuate section and engaging both the first bearing and the second bearing.

- 5 Conveniently, the first arcuate section engages both the first bearing and the second bearing.

 Preferably, the arcuate sections are interconnected by two relatively narrow interconnecting bridges.

10

 Advantageously, the second retaining element is of annular form, the element carrying a plurality of radially inwardly directed resilient lugs which engage the first bearing on which the steering wheel is mounted, the second retaining element being secured to part of the steering wheel.

15

 Conveniently, the second retaining element is provided with a plurality of fixing studs, the fixing studs passing through corresponding apertures formed in part of the steering wheel.

20

 In order that the invention may be more readily understood, and so that further features thereof may be appreciated, an embodiment of the invention will now be described, by way of example, with reference to the accompanying drawings in which:

25

 Fig. 1 is a perspective view of a steering wheel arrangement, parts of which are shown cut-away;

 Fig. 2 is a sectional view illustrating part of the steering wheel mounting in more detail;

Fig. 3 is a further sectional view taking on the line III-III of Fig. 2;

Fig. 4 is a perspective view of a fixed element of a modified design;

Fig. 5 is a view of the element of Fig. 4 from the opposite side; and

Fig. 6 is a sectional view of the fixed element.

10 A steering wheel assembly 1 is illustrated which incorporates a steering-wheel 2, mounted on a steering column 3. A fixed housing 4 is provided which is securely mounted in position.

15 The steering wheel 3 incorporates a metal frame 5 which defines spokes such as spokes 6, and a peripheral rim 7. The frame 5 is covered with an appropriate outer covering 8, for example, of a foam material.

20 The frame 5 is mounted by means of an annular bearing 9 on an appropriate formation provided on the housing 4. The steering wheel is to rotate about a predetermined axis. An air-bag unit 10 may be provided, which is connected directly to the fixed element 4. The air-bag unit 10 will thus not rotate on rotation of the steering wheel. The air-bag unit may be provided with a plurality of operating buttons 11 or the like, which will be fixed in position.

25 Part of the frame 5 adjacent to the annular bearing 9 defines an inwardly-facing gear 12.

The steering column 3 is mounted within a tubular projection 13 which extends downwardly from the rest of the housing 4 by means of two spaced-

apart bearings 14, 15 (see Fig. 1). The uppermost end of the steering column, carries a pinion 16, the pinion having a toothed periphery 17 which engages with the ring gear 12 provided on the steering wheel frame.

5 It will be understood that on rotation of the steering wheel, the pinion 16 will rotate, thus rotating the steering column. A steering wheel assembly of this general type has been proposed before, and is described in EP-A-1199243.

10 It is to be observed that in the prior proposed arrangement described above, the bearings 14,15 between the fixed housing 4 and the steering column 3 are offset from the bearing 9 between the fixed housing 4 and the steering wheel frame. This offset of bearings can provide some degree of "play" which is undesirable. It has been proposed, therefore, to provide an arrangement in which the bearings are coplanar or substantially coplanar in their relative
15 positioning. However, if an arrangement of this type is utilised it may be found difficult to mount the bearings in position.

However, referring now to Figs 4 to 6, which illustrate a fixed element for mounting a steering wheel, which embodies the invention, an arrangement
20 has been devised in which the bearings are coplanar, but yet the bearings can readily be mounted in position.

Referring initially to Figs. 4 and 5, a fixed element 20 is provided. The fixed element 20 has a rectangular base presenting two oppositely directed
25 mounting flanges 21, 22. Each mounting flange is provided with appropriate mounting apertures 23, to enable the fixed element 20 to be readily fixed in position. The mounting flanges 21,22 support an upwardly directed hollow housing 24. The housing 24, because of its intended location, has a relatively complex external form, but the form of the housing is not relevant to the

present invention. The upper part of the housing 24 presents an upper surface 25. The upper surface 25 is divided into two arcuate regions 26, 27 each of substantially semicircular extent and which are each at different levels. The upper surface 25 thus has a substantially circular exterior side wall 28. As will
5 become clear from the following description, the side wall 28 engages part of a bearing.

The arcuate region 26, which is the higher of the two, is provided with two apertures 26A, 26B, and the arcuate region 27 is provided with two similar
10 apertures 27A, 27B.

A circular opening 29 is formed in the upper surface 25 of the housing, the opening 29 having an inwardly directed annular side wall 30. The wall 30, as will become clear in the following description, forms a seat for another
15 bearing.

The opening 29 is offset from the centre of the circular upper surface 25.

Turning now to Fig. 6, part 31 of a steering wheel frame is illustrated.
20 The part 31 is of annular form and defines, on its inner face, an annular ring gear 32. Beneath the ring gear 32 the annular part of the steering wheel frame 31 is supported on an annular ring bearing 33. The annular ring bearing 33 is mounted on the outer side wall 28 of the upper surface 25 of the housing.

25 A pinion 34 is provided. The pinion 34 has a toothed exterior 35. The toothed exterior of the pinion 34 engages the toothed ring gear 32 provided on the annular part 31 of the steering wheel frame. The pinion 34 is provided with a hollow mounting shaft 36 the interior of which is splined 37. The pinion is mounted by means of an annular ring bearing 38, the ring bearing 38 engaging

the exterior of the mounting shaft 36 and also being received within the opening 29. The ring bearing thus engages the side wall 30 of the opening 29.

It is to be noted, therefore, that a ring bearing 33 is mounted on the exterior wall 28 of the upper part 25 of the housing 24, and a further ring bearing 38 is accommodated within the opening 29.

A securing plate 40 is provided which extends over the bearings to retain the bearings in position. Of course, a further engagement will be provided on the steering wheel frame to engage the bearing 33, but this is not shown for the sake of simplicity of illustration.

A further retaining element 41 is provided which serves to retain the bearing 33. The retaining elements 40, 41 are described in more detail below with reference to Figs. 7 to 10.

Retaining element 40, as shown in Fig. 7, comprises an element formed from a circular plate 42. A relatively large aperture 43 is provided in the plate, slightly offset from the centre. The aperture 43 is configured to lie adjacent the opening 29 formed in the housing 24 and thus has a similar overall size to the opening 29. Parts of the aperture 43, however, approach the periphery of the plate, and serve to leave only two narrow necks 44, 45, the necks 44, 45 thus effectively serving to join together two arcuate areas 45¹, 46 of the plate. The arcuate area 45¹ is located to one side of the central aperture 43 and carries two depending mounting studs 47, 48. The other arcuate part 46 is crescent shaped, and lies to the other side of the aperture 43.

The narrow necks 44, 45 have resilient properties, and thus the arcuate region 46 may move resiliently relative to the arcuate region 45¹.

It is to be appreciated that the two mounting studs 47, 48 pass through the apertures 26A, 26B in the area 26 of the upper surface 25 on the housing 24 which is the higher of the two upper surfaces in the orientation shown in Fig. 4.

5 Part of the arcuate region 45¹ will thus overlie the periphery of the opening 29, serving to lie over the bearing 38 when it has been located within the opening 29. That part of the plate may be drawn tightly into engagement with the bearing.

10 The crescent shaped arcuate part 46 of the plate 40, which overlies the region 27 of the upper surface 25 which is the lower of the two regions, will be biased downwardly towards that region, to resiliently engage the region and the part of the crescent shaped area 46 which bounds the aperture 43 will thus overlie a further part of the bearing 38 which is located in the opening 29
15 formed in the upper part of the housing 24. This part will resiliently engage the bearing and help ensure that the bearing is maintained in position within the opening 29 in a "rattle-free" manner.

The outermost part of the arcuate portion 45, that is to say the radially
20 outermost part, will overlie part of the bearing 33 which supports the steering wheel frame, at a point where the opening 29 is located adjacent the peripheral side wall 28 formed at the upper part of the housing 24. Thus, this will help maintain the bearing 33 in position. Similarly, a peripherally outermost part of the crescent shaped arcuate region 46 will also overlie part of the bearing 33,
25 but will be resiliently biased into contact with the bearing 33, thus helping maintain the bearing in position in a rattle-free manner.

The second retaining element 41 is shown in Figs. 9 and 10. The retaining element 41 is of annular form, being formed of a plate-like material

and having four substantially equi-angularly spaced retaining studs 49, 50, 51, 52. At positions between the studs there are resiliently yieldable inwardly directed tabs 53, 54, 55, 56. The tabs are deflected from the plane of the annular plate in the same direction as the direction of the studs.

5

The retaining element 41 is mounted in position with the yieldable tabs 53,54,55,56 engaging the under-surface of the steering wheel bearing 33, the retaining studs, such as stud 49 passing through appropriate apertures formed in a region of the steering wheel frame 57 that surrounds the annular part 31 that carries the ring gear 32 (see Fig. 6).

10

As can be seen, the resilient tabs, such as tab 55 shown to the left-hand side of Fig. 6, resiliently engage the bearing 33 to hold the bearing in position in a rattle-free manner.

15

When used in this specification and claims, the terms "comprises" and "comprising" and variations thereof mean that the specified features, steps or integers are included. The terms are not to be interpreted to exclude the presence of other features, steps or components.

20

The features disclosed in the foregoing description, or the following claims, or the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms thereof.

25

CLAIMS:

- 5 1. A steering wheel arrangement, the steering wheel arrangement incorporating a fixed element, the fixed element carrying a first annular bearing, the annular bearing supporting a steering wheel for rotation relative to the fixed element, the fixed element also carrying a second bearing, the second bearing rotatably supporting a component to be connected to part of the steering
10 column of a vehicle, the bearings each being retained, to the fixed element, by means of a first resilient retaining element, and the first bearing being retained to the steering wheel by a second resilient retaining element.
- 15 2. An arrangement according to Claim 1 wherein the fixed element has a housing part with an upper surface, the upper surface having at least two levels, the outer periphery of the upper surface defining a wall, the first bearing being mounted to that wall, the upper surface defining an opening having a side wall, the second bearing being mounted to that side wall; wherein the first retaining
20 element comprises a plate which lies over the upper surface, the plate having a part which is resiliently biased into contact with part of the first bearing and with part of the second bearing.
- 25 3. An arrangement according to Claim 2 wherein the plate has two arcuate sections located to either side of an aperture, one arcuate section being provided with retaining studs to secure the plate to the fixed element, the other arcuate section being resiliently connected to the first arcuate section and engaging both the first bearing and the second bearing.

4. An arrangement according to Claim 3 wherein the first arcuate section engages both the first bearing and the second bearing.
5. An arrangement according to Claim 3 or 4 wherein the arcuate sections are interconnected by two relatively narrow interconnecting bridges.
6. An arrangement according to any preceding Claim wherein the second retaining element is of annular form, the element carrying a plurality of radially inwardly directed resilient lugs which engage the first bearing on which the steering wheel is mounted, the second retaining element being secured to part of the steering wheel.
7. An arrangement according to Claim 6 wherein the second retaining element is provided with a plurality of fixing studs, the fixing studs passing through corresponding apertures formed in part of the steering wheel.
8. A steering wheel arrangement substantially as herein described with reference to and as shown in Figs. 4 to 10 of the accompanying drawings.
9. Any novel feature or combination of features disclosed herein.

ABSTRACT

5

**“IMPROVEMENTS IN OR RELATING TO A STEERING WHEEL
ARRANGEMENT”**

10

A steering wheel arrangement is disclosed which incorporates a fixed element (20). The fixed element carries a first annular bearing (33) which supports a steering wheel for rotation relative to the fixed element (20). The fixed element also carries a second bearing (38) which rotatably supports a component to be
15 connected to part of the steering column of a motor vehicle. Each of the bearings are retained, to the fixed element (20), by means of a first resilient retaining element (40), and the first bearing (33) is also retained to the steering wheel by a second resilient retaining element (41).

20

FIGURE 6.




FIG 1






FIG 2






FIG 3






FIG. 4




FIG. 5



FIG 6






FIG 8





FIG 7








FIG. 10

FIG. 9

